



TYPICAL DATA SHEET | ISSUE DATE | FEB-15

GRADE	WWW.TPCO.IR
HD3840UA***	IRAN/TABRIZ/TABRIZ PETROCHEMICAL COMPANY/P.O.BOX:51745- 354/TEL:+984134282612

HD3840UA is high density polyethylene copolymer containing butene-1(C4) as comonomer. It is suitable for use as rotational moulding applications. HD3840UA has the following characteristics:
good impact strength,easy to demould,uv stabilised,good whiteness,excellent surface finish.

Applications:

general purpose rotomolded items,septic tanks,recycling banks

PROPERTY	UNIT	TEST METHOD	TYPICAL VALUE
MELT FLOW INDEX(2.16KG)	g/10min	ASTM D-1238	4
DENSITY	gr/cm3	ASTM D-1505	0.938
YELLOWNESS INDEX	--	ASTM E-313	-1
WHITENESS INDEX	--	ASTM E-313	60
CONTAMINATION	NO	BP137	5
TENSILE STRESS AT YEILD	MPA	ASTM D-638	15
ELONGATION AT BREAK	%	ASTM D-638	900
ESCR(IGEPAL10% F50,23°C)	HR	ASTM D-1693	350
CHARPY IMPACT	KJ/M2	ASTM D-6110	18



Adress İzzetpaşa Mahallesi, Yeni yol Caddesi, No: 3,
Kat 3 Ofis No. 303Nurul Tower Şişli,Vstanbul /Turkey



Tel +90 2129 827 486
Fax +90 8505 223 403
Mob +90 534 271 38 22



Website www.RGMPETROKIMYA.com
Email Commercial@rgmpetrokimya.com
WhatsApp & Telegram @RGM

RGM



*All above mentioned data are typical values and not to be construed as real specifications. Users should confirm results by their own tests. For more information about guaranteed items, please refer to S.S.S. (Standard Sales Specifications)

**Rotomoulded Bucket-23 Liters-3mm Thickness-1.2Kg

Grade Suffix (Additives Indication):

UA: GENERAL ANTIOXIDANT AND LIGHT STABILISER

*** HD3840UA falls into the density range of MDPE. However, in order to observing the nomenclature procedure of PE plant licensor (INEOS), this grade is designated as HDPE; while it can be introduced as MD3840UA as well

PROPERTY	UNIT	TEST METHOD	SPECIFICATION RANGE
MELT FLOW INDEX (2.16KG)	g/10min	ASTM D-1238	3.8-4.5
DENSITY	gr/cm ³	ASTM D-1505	0.935-0.939
CONTAMINATION	NO.	BP137	≤5 DEFECTS IN 200GR OF PELLETS

*FOR MORE INFORMATION PLEASE CALL QUALITY ASSURANCE DEPARTMENT AT ABOVE ADDRESS



Adress İzzetpaşa Mahallesi, Yeni yol Caddesi, No: 3,
Kat 3 Ofis No. 303Nurul Tower Şişli, İstanbul / Turkey



Tel +90 2129 827 486
Fax +90 8505 223 403
Mob +90 534 271 38 22



Website www.RGMPETROKIMYA.com
Email Commercial@rgmpetrokimya.com
WhatsApp & Telegram @RGM

RGM



PROPERTY	UNIT	TEST METHOD	SPECIFICATION RANGE
BEAD SIZE	MM	SUNPOR 7 2 5 (MIN 90% BY WT)	1-1.8
K-VALUE	--	SUNPOR 7.2.4	52-57
PENTANE CONTENT	WT%	SUNPOR 7.2.2	MIN 5.2
MOISTURE CONTENT	WT%	SUNPOR 7.2.3	MAX 1
RESIDUAL MONOMER	PPM	SUNPOR 7.2.1	MAX 1000

* FOR MORE INFORMATION PLEASE CALL QUALITY ASSURANCE DEPARTMENT AT ABOVE ADDRESS.



Adress İzzetpaşa Mahallesi, Yeni yol Caddesi, No: 3,
Kat 3 Ofis No. 303Nurol Tower Şişli,Vstanbul /Turkey



Tel +90 2129 827 486
Fax +90 8505 223 403
Mob +90 534 271 38 22



Website www.RGMPETROKIMYA.com
Email Commercial@rgmpetrokimya.com
WhatsApp & Telegram @RGM

RGM



TYPICAL DATA SHEET | ISSUE DATE | FEB-15

GRADE	WWW.TPCO.IR
HD3840UA***	IRAN/TABRIZ/TABRIZ PETROCHEMICAL COMPANY/P.O.BOX:51745- 354/TEL:+984134282612

HD3840UA is high density polyethylene copolymer containing butene-1(C4) as comonomer. It is suitable for use as rotational moulding applications. HD3840UA has the following characteristics:
good impact strength,easy to demould,uv stabilised,good whiteness,excellent surface finish.

Applications:

general purpose rotomolded items,septic tanks,recycling banks

PROPERTY	UNIT	TEST METHOD	TYPICAL VALUE
MELT FLOW INDEX(2.16KG)	g/10min	ASTM D-1238	4
DENSITY	gr/cm3	ASTM D-1505	0.938
YELLOWNESS INDEX	--	ASTM E-313	-1
WHITENESS INDEX	--	ASTM E-313	60
CONTAMINATION	NO	BP137	5
TENSILE STRESS AT YEILD	MPA	ASTM D-638	15
ELONGATION AT BREAK	%	ASTM D-638	900
ESCR(IGEPAL10% F50,23°C)	HR	ASTM D-1693	350
CHARPY IMPACT	KJ/M2	ASTM D-6110	18



Adress İzzetpaşa Mahallesi, Yeni yol Caddesi, No: 3,
Kat 3 Ofis No. 303Nurul Tower Şişli,Vstanbul /Turkey



Tel +90 2129 827 486
Fax +90 8505 223 403
Mob +90 534 271 38 22



Website www.RGMPETROKIMYA.com
Email Commercial@rgmpetrokimya.com
WhatsApp & Telegram @RGM

RGM