



## HIPS-6045

High Impact Polystyrene for Extrusion and Injection molding

### PRODUCT DESCRIPTION

HIPS-6045 gives excellent extrusion .also it can be use for injection molding.

### TYPICAL APPLICATIONS

It use for wide range of injection molding applications ,office ,kitchen and bathroom articles.

It use for wide range of extrusion, food packaging as beverage cups, packaging for dairy products ,for sheet, disposable dishware, toys , internal parts and housings of household.

### TYPICAL DATA

PROPERTIES	UNIT	VALUE	ASTM METHOD
physical			
Melt flow rate @200°C & 5 kg load	g/10min	4	D1238
Mechanical properties			
Tensile strenght	Mpa	24	D638
Flexural modulus	Mpa	1900	D790
Charpy impact strength	Kj/m <sup>2</sup>	9.5	ISO180
Thermal properties			
Vicat softening point @120°C,1 kg	°C	91	D1525

Note: All mechanical properties measured under standard conditions 50% RH and 23C.

### PACKING

HIPS-6045 is supplied in the form of cylindrical of approximately 2.5×2.5 mm. the material can be supplied in either 25 kg bags.

### REGULATORY INFORMATION

It is responsibility of the manufacturers of food contact articles and industrial food packers to make sure the article in their actual use are in compliance with the imposed migration requirements.



Adress İzzetpaşa Mahallesi, Yeni yol Caddesi, No: 3,  
Kat 3 Ofis No. 303Nurol Tower Şişli,Vstanbul /Turkey



Tel +90 2129 827 486  
Fax +90 8505 223 403  
Mob +90 534 271 38 22



Website [www.RGMPETROKIMYA.com](http://www.RGMPETROKIMYA.com)  
Email [Commercial@rgmpetrokimya.com](mailto:Commercial@rgmpetrokimya.com)  
WhatsApp & Telegram @RGM

RGM